



Caulking is a heavybodied, elastomeric patching compound. This trowel-grade material fills cracks and termination points and seals around roof openings and protrusions.

It creates durable, waterproof seams. Used alone or used with Base Coat, Finish Coat...it adds years of life to watertight surfaces.

Caulking used with mesh fabric creates extra reinforcement to structural stress areas. As these areas expand and contract in response to various weather conditions so will the Caulking. It is elastomeric, remaining flexible in weather down to -20°F.

Caulking is easy to apply with a bulk caulking gun, trowel, putty knife, or roofing brush. Cleanup is easy too, with just warm water and soap.

FEATURES

Elastomeric

Caulking rubber-like, elastic consistency permits it to remain flexible in the most severe weather conditions, down to -20°F. It expands and contracts with the surface surrounding it.

Waterproof

Caulking not only fills leaking cracks and seams to prevent them

from further leaking, but also inherently prevents leakage by being a waterproofing material itself. It adds years of life to watertight surfaces.

Adhesion

It bonds tenaciously to all properly prepared surfaces. Susceptibility to intercoat leakage and breakdown does not exist. The tight bond between Caulking and Base Coat makes it impossible to separate at the layer junctions.

Reinforcement

When used with mesh fabric Caulking creates optimal reinforcement for cracks, joints, and other high stress areas.

10 Year Warranty

Caulking is warranted for 10 years from the date of application.

Ready to Use/Easy Application

Caulking is ready to use. Apply with a bulk caulking gun, trowel, putty knife, or roofing brush.